



(A) Unless otherwise specified upon order, Customer Required Clearance is automatically set to 2 mm by Pulseroller USA Order Entry System

INCLUDED ITEMS		
ITEM	DESCRIPTION	QTY
1		0
2	M12 X 1.25 FLANGE HEX NUT 50 NM TIGHTENING TORQUE	1

PR-AD-48-xxx-xxZRAP	
TUBE DIA	48.6 mm
INTERLOCK	NONE - PLAIN STRAIGHT
MOTOR END	M12 THREADED SHAFT
IDLER END	SPRING LOADED HEX
CONNECTOR	4-PIN M8

xxx = RL in mm
xx = Speed Code

PULSEROLLER
WEB: WWW.PULSEROLLER.COM
EMAIL: SALES@PULSEROLLER.COM

REV.	DATE	DESCRIPTION	DATE	21-MAR-2024	DESIGNED BY:	SCALE	NONE	SHEET:	1 OF 1	DWG. NO.	PR-AD-48-xxx-xxZRAP	REV:

THE INFORMATION CONTAINED HEREIN IS CONFIDENTIAL AND IS SUBMITTED IN CONFIDENCE. PULSEROLLER AND SHALL BE USED ONLY IN CONNECTION WITH AND PERFORMANCE OF PULSEROLLER PRODUCTS. NO PART, WHOLE OR IN WHOLE OR IN PART BY OTHERS.