



Installation

Tightening torque (M6) : 70.8-88.5 in-lb (8 - 10 N-m)

Tightening torque (M5) : 20.4-30.9 in-lb (2.3 - 3.5 N-m)



REV.	DATE	DESCRIPTION	DATE	DESIGNED BY	CHECKED BY	SCALE	SHEET	TITLE	DWG. NO.	REV.
A	21-MAY-2020	CONVERTED TO METRIC, UPDATE TITLE BLOCK	21-MAR-2015	JPK		NONE	1 OF 1	FIXING BRACKET - FLAT UP SHORT	PR-D-30H-FU-N-ST	C
B	05-APR-2021	CORRECTED DIMENSIONS						PART NUMBER PR-D-30H-FU-N-ST		
C	10-APR-2024	UPDATED M5 FASTENERS						FOR: SENERGY ACCESSORIES		
								PULSEROLLER STANDARDS		

THE INFORMATION CONTAINED HEREIN IS CONFIDENTIAL, IS SUBMITTED IN CONFIDENCE, AND IS PROPRIETARY INFORMATION OF PULSEROLLER AND SHALL BE USED ONLY IN CONJUNCTION WITH AND PERFORMANCE OF THE CONTRACT OF WHICH THIS DRAWING FORMS A PART, AND SHALL NOT, WITHOUT PULSEROLLER PRIOR WRITTEN APPROVAL, BE REPRODUCED OR IN ANY OTHER WAY USED IN WHOLE OR IN PART BY OTHERS.