



Unless otherwise specified upon order, Customer
 (A) Required Clearance is automatically set to 2 mm by
 Pulseroller USA Order Entry System

INCLUDED ITEMS		
ITEM	DESCRIPTION	QTY
1		0
2	PR-D-30H-XX-(XX) MOTOR SHAFT FIXING BRACKET - SPECIFY AT TIME OF ORDER	1

PR-AD-48-xxx-xxZxFQ	
TUBE DIA	48.6 mm
INTERLOCK	ROUND GROOVE PULLEY
MOTOR END	NON THREADED HEX SHAFT
IDLER END	SPRING LOADED HEX
CONNECTOR	JST (S) OR M8 (M)

xxx = RL in mm
 xx = Speed Code



REV.	DATE	DESCRIPTION
E	24-JAN-2023	COMBINED JST & AI TO SAME DWG, UPDATED DWG NUMBER
B	15-DEC-2020	ADDED CUSTOMER REQUIRED CLEARANCE
C	10-MAY-2021	CORRECTED LENGTH FORMULA
D	06-JUL-2021	ADDED DESCRIPTION CHART AND FIXING BRACKET

THE INFORMATION CONTAINED HEREIN IS CONFIDENTIAL, IS SUBMITTED IN CONFIDENCE, AND IS PROPRIETARY INFORMATION OF PULSEROLLER AND SHALL BE USED ONLY IN CONJUNCTION WITH AND PERFORMANCE OF THE CONTRACT OF WHICH THIS DRAWING FORMS A PART, AND SHALL NOT, WITHOUT PULSEROLLER PRIOR WRITTEN APPROVAL, BE REPRODUCED OR IN ANY OTHER WAY USED IN WHOLE OR IN PART BY OTHERS.

DATE:	21-MAR-2014
DESIGNED BY:	
CHECKED BY:	
SCALE:	NONE
SHEET:	1 OF 1

TITLE:	STANDARD 48 DIA ROUND GROOVE PULLEY PART NUMBER PR-AD-48-xxx-xxZxFQ
FOR:	SENERGY MOTOR ROLLER PULSEROLLER STANDARDS
DWG. NO:	PR-AD-48-xxx-xxZxFQ
REV:	E