



Unless otherwise specified upon order, Customer  
 (A) Required Clearance is automatically set to 2 mm by  
 Pulseroller USA Order Entry System

INCLUDED ITEMS		
ITEM	DESCRIPTION	QTY
1		0
2	PR-D-30H-XX-(XX) MOTOR SHAFT FIXING BRACKET - SPECIFY AT TIME OF ORDER	1

PR-AD-48-xxx-xxZxHQ	
TUBE DIA	48.6 mm
INTERLOCK	MICRO-V HUB
MOTOR END	NON THREADED HEX SHAFT
IDLER END	SPRING LOADED HEX
CONNECTOR	JST (S) OR M8 (M)

xxx = RL in mm  
 xx = Speed Code



**PULSEROLLER**  
 WEB: WWW.PULSEROLLER.COM  
 SUPPORT: SUPPORT@PULSEROLLER.COM  
 SALES: SALES@PULSEROLLER.COM

REV.	DATE	DESCRIPTION	✓
A	20-MAY-2020	UPDATED DIMENSIONS TO METRIC	
B	15-DEC-2020	ADDED CUSTOMER REQUIRED CLEARANCE	
C	06-JUL-2021	ADDED DESCRIPTION CHART AND FIXING BRACKET	
D	24-JAN-2023	COMBINED JST & AI INTO ONE DWG, UPDATED DWG NUMBER	

DATE: 21-MAR-2014	TITLE: STANDARD 48 DIA MICRO-V
DESIGNED BY:	PART NUMBER PR-AD-48-xxx-xxZxHQ
CHECKED BY:	FOR: SENERGY MOTOR ROLLER
SCALE: NONE	PULSEROLLER STANDARDS
SHEET: 1 OF 1	DWG. NO: PR-AD-48-xxx-xxZxHQ
	REV: D

THE INFORMATION CONTAINED HEREIN IS CONFIDENTIAL, IS SUBMITTED IN CONFIDENCE, AND IS PROPRIETARY INFORMATION OF PULSEROLLER AND SHALL BE USED ONLY IN CONJUNCTION WITH AND PERFORMANCE OF THE CONTRACT OF WHICH THIS DRAWING FORMS A PART, AND SHALL NOT, WITHOUT PULSEROLLER PRIOR WRITTEN APPROVAL, BE REPRODUCED OR IN ANY OTHER WAY USED IN WHOLE OR IN PART BY OTHERS.