



Precaution
 Tightening torque (M6) : 70.8-88.5 (Lbf in)
 Tightening torque (M5) : 20.4-30.9 (Lbf in)

REV.	DATE	DESCRIPTION	<p>THE INFORMATION CONTAINED HEREIN IS CONFIDENTIAL, IS SUBMITTED IN CONFIDENCE, AND IS PROPRIETARY INFORMATION OF PULSEROLLER AND SHALL BE USED ONLY IN CONNECTION WITH AND PERFORMANCE OF THE CONTRACT OF WHICH THIS DRAWING FORMS A PART, AND SHALL NOT, WITHOUT PULSEROLLER PRIOR WRITTEN APPROVAL, BE REPRODUCED OR IN ANY OTHER WAY USED IN WHOLE OR IN PART BY OTHERS.</p>
A	21-MAY-2020	CONVERTED TO METRIC, UPDATE TITLE BLOCK	<p>DATE: 21-MAR-2015</p> <p>DESIGNED BY: JPK</p> <p>CHECKED BY:</p> <p>SCALE: NONE</p> <p>SHEET: 1 OF 1</p>
<p>TITLE: FIXING BRACKET - POINT UP STANDARD PART NUMBER PR-D-30H-PU-N</p> <p>FOR: SENERGY ACCESSORIES PULSEROLLER STANDARDS</p>			<p>DWG. NO.: PR-D-30H-PU-N</p> <p>REV.: A</p>

