



Ⓐ Unless otherwise specified upon order, Customer Required Clearance is automatically set to 2 mm by Pulseroller USA Order Entry System

INCLUDED ITEMS	
ITEM	DESCRIPTION
1	M12 X 1.25 FLANGE HEX NUT
2	50 NM TIGHTENING TORQUE

PR-AD-48-xxx-xxZRG	
TUBE DIA	48.6 mm
INTERLOCK	ROUND GROOVE
MOTOR END	M12 THREADED SHAFT
IDLER END	SPRING LOADED HEX CONNECTOR

xxx = RL in mm
xx = Speed Code

PULSEROLLER
WEB: WWW.PULSEROLLER.COM
EMAIL: SALES@PULSEROLLER.COM

REV.	DATE	DESCRIPTION	CHECKED BY:	SCALE	NONE	SHEET:	1 OF 1	DWG. NO.	PR-AD-48-xxx-xxZRG	REV:

DATE: 21-MAR-2024
DESIGNED BY:
CHECKED BY:
SCALE: NONE
SHEET: 1 OF 1

TITLE: STANDARD 48 DIA ROUND GROOVE
PART NUMBER PR-AD-48-xxx-xxZRG
FOR: RAPTOR-AI-ST MOTOR ROLLER
PULSEROLLER STANDARDS

THE INFORMATION CONTAINED HEREIN IS CONFIDENTIAL AND IS SUBMITTED IN CONFIDENCE. PULSEROLLER AND SHALL BE USED ONLY IN CONNECTION WITH THE PERFORMANCE OF THE PULSEROLLER FROM WHICH IT WAS OBTAINED. NO PART AND SHALL NOT, WITHOUT PULSEROLLER'S PRIOR WRITTEN APPROVAL, BE REPRODUCED OR TRANSMITTED IN ANY FORM OR BY ANY MEANS, ELECTRONIC OR MECHANICAL, INCLUDING PHOTOCOPYING, RECORDING, OR BY ANY INFORMATION STORAGE AND RETRIEVAL SYSTEM. PULSEROLLER SHALL BE USED IN WHOLE OR IN PART BY OTHERS.