



Ⓐ Unless otherwise specified upon order, Customer Required Clearance is automatically set to 2 mm by Pulseroller USA Order Entry System

INCLUDED ITEMS		
ITEM	DESCRIPTION	QTY
1		0
2	M12 X 1.25 FLANGE HEX NUT 50 NM TIGHTENING TORQUE	1

PR-AD-48-xxx-xxZRHP	
TUBE DIA	48.6 mm
INTERLOCK	MICRO-V HUB
MOTOR END	M12 THREADED SHAFT
IDLER END	SPRING LOADED HEX
CONNECTOR	4-PIN M8

xxx = RL in mm
xx = Speed Code

PULSEROLLER
WEB: WWW.PULSEROLLER.COM
EMAIL: SALES@PULSEROLLER.COM

REV.	DATE	DESCRIPTION

DATE:	21-MAR-2024	TITLE:	STANDARD 48 DIA MICRO-V HUB
DESIGNED BY:		FOR:	PART NUMBER PR-AD-48-xxx-xxZRHP
CHECKED BY:			RAPTOR-AI-ST MOTOR ROLLER
SCALE:	NONE		PULSEROLLER STANDARDS
SHEET:	1 OF 1	DWG. NO.:	PR-AD-48-xxx-xxZRHP
		REV.:	

THE INFORMATION CONTAINED HEREIN IS CONFIDENTIAL AND IS NOT TO BE DISCLOSED OR REPRODUCED IN ANY MANNER WITHOUT THE WRITTEN APPROVAL OF PULSEROLLER. PULSEROLLER SHALL NOT BE HELD RESPONSIBLE FOR ANY DAMAGE TO PROPERTY OR PERSONS ARISING FROM THE USE OF THIS INFORMATION. PULSEROLLER SHALL NOT BE HELD RESPONSIBLE FOR ANY DAMAGE TO PROPERTY OR PERSONS ARISING FROM THE USE OF THIS INFORMATION.